



### TimberFix Tek's drill, tap and fasten in one operation

The original self drilling, self tapping screw to fasten timber to steel.

### Product Advantages

- Tek's screws drill, tap and fasten in one operation
- No hole alignment issues
- High clamping action
- Eliminates the need for costly drill bits
- Excellent driving stability
- Point to thread design maximises pullout performance
- Non walking point provides fast material engagement
- Sharp convex drill point has precise cutting edges to improve drill performance with less effort
- Climaseal finish provides excellent corrosion resistance and lower tapping torque

### Specification

Wing Tek's Screws fasten timber, plywood, chipboard and similar materials to metal. The wings ream a clearance hole in the wood to prevent thread engagement and jacking. The Tek's point drills the steel, then the wings break off enabling the threads to engage and the fastener to clamp the wood firmly to the steel.

Timber-Fix must penetrate through the steel to expose at least two full threads. Timber-Fix wings must be driven into a minimum of 1.5mm steel thickness to allow wings to break consistently.

### Head Styles



- A. Countersunk Ribbed
- B. Wafer
- C. Countersunk
- D. Wafer Ribbed

### Applications

- Timber Frame erection
- Roofing
- Joists
- Wall plate
- Floor boarding
- Metal construction



## TimberFix Screws

### Product Range - TimberFix - For Applications to Steel



Eurocode	Code	Head Style	Diameter	Length	Timber Thickness	Steel Thickness	Box Qty
921200	TFC36	P2 Wafer	4.8mm	36mm	0.9 - 3.0mm	1.5 - 3.0mm	100
921294	TFC38	P2 CSK Ribbed	4.8mm	38mm	0.9 - 3.0mm	1.5 - 3.0mm	100
921295	TFC45	P2 CSK Ribbed	4.8mm	45mm	0.9 - 3.0mm	1.5 - 3.0mm	100
921296	TFC50	P3 CSK Ribbed	5.5mm	50mm	1.2 - 5.0mm	1.5 - 3.0mm	100
921297	TFC61	P3 CSK Ribbed	5.5mm	61mm	1.2 - 5.0mm	1.5 - 3.0mm	100
921298	TFC80	P3 Wafer	5.5mm	80mm	1.2 - 5.0mm	1.5 - 3.0mm	100
921292	TFC100	P3 Wafer	5.5mm	100mm	1.2 - 5.0mm	1.5 - 3.0mm	100
921293	TFC120	P3 Wafer	5.5mm	120mm	1.2 - 5.0mm	1.5 - 3.0mm	100

### Product Range - TimberFix - For Applications to Steel



Eurocode	Code	Head Style	Diameter	Length	Timber Thickness	Steel Thickness	Box Qty
920029	TFM57	P3 CSK	5.5mm	57mm	18 - 35mm	4.0 - 6.0mm	250
920030	TFM70	P3 CSK	5.5mm	70mm	18 - 40mm	4.0 - 6.0mm	250
920031	TFM75	P3 CSK	6.3mm	75mm	18 - 50mm	4.0 - 6.0mm	200

### Product Range - TimberFix - For Applications to Steel



Eurocode	Code	Head Style	Diameter	Length	Timber Thickness	Steel Thickness	Box Qty
921300	TFL42	P3 CSK	5.5mm	42mm	10 - 13mm	4.0 - 10.0mm	100
921301	TFL65	P3 CSK	5.5mm	65mm	10 - 28mm	4.0 - 10.0mm	100
921302	TFL80	P3 CSK	5.5mm	80mm	10 - 42mm	4.0 - 10.0mm	100
921303	TFL90	P3 Wafer	5.5mm	90mm	35 - 55mm	4.0 - 10.0mm	100
921299	TFL100	P3 Wafer	5.5mm	100mm	45 - 65mm	4.0 - 10.0mm	100