

Tool Details: Impulse IM65 F16



Tool Type:	Gas Nailer
Manufacturer:	Paslode
Power Source:	Battery / Fuel Cell
Weight:	2.3 kg
Other Info:	Cordless Straight Brad Nailer

Tool Vibration and Performance Analysis

Appendage: Paslode Galvanised Angle Brad - F16 x 32 mm (921588)
Test Date: 12/01/2007

Description of Performance Work Unit:	Driving brads into 19 mm softwood skirting / softwood (simulation laying of skirting, 30 cycles per repeat)
Time to achieve work unit:	26.7 secs
Vibration magnitude:	9 m/s ²
Standard Deviation:	0.58 m/s ²
Cycles to reach EAV:	2478 brads
Cycles to reach ELV:	9911 brads
HSE points per work unit:	1.21 points
HSE points per hour of tool use:	163 points

Appendage: Paslode Galvanised Angle Brad - F16 x 38 mm (300271)
Test Date: 12/01/2007

Description of Performance Work Unit:	Driving brads into 19 mm MDF / softwood (simulation laying of skirting, 30 cycles per repeat)
Time to achieve work unit:	26.7 secs
Vibration magnitude:	8.9 m/s ²
Standard Deviation:	1.51 m/s ²
Cycles units to reach EAV:	2557 brads
Cycles units to reach ELV:	10228 brads
HSE points per work unit:	1.17 points
HSE points per hour of tool use:	158 points

Contact Information