

Teks Self Drilling Steel Screws



The original self-drilling, self-tapping screw for fastening various materials to steel

Teks Screws drill, tap and fasten in-one operation.

Installation Equipment

- Electric screw gun (SPIT 216 Drywall Screw Gun)

Applications

- Brick ties
- Bracketry to steel
- Flashing
- Composite panels
- Wind posts

Installation

1. Using the chart below, select the appropriate Teks screw based on steel thickness and fixture thickness.
2. Using an electric screwgun with an RPM range of 0 - 2000 and a depth sensitive nosepiece, drive screw until flush with fixture.

Product Range - Teks Screws for General Components to Steel

Eurocode	Code	Steel Thickness	Effective Thread Length	Diameter	Length	Head Style
921185	PH14	1.2 - 3.0mm	4mm	4.8mm	14mm	Pan head
920026	TC13	1.5 - 2.0mm	4mm	4.8mm	13mm	5 / 6" AF HEX
920027	TC16	1.2 - 3.5mm	6mm	4.8mm	16mm	5 / 6" AF HEX
920028	TC25	1.2 - 3.5mm	8mm	5.5mm	25mm	5 / 6" AF HEX
920126	TC50	1.2 - 3.5mm	42mm	5.5mm	50mm	5 / 6" AF HEX
920127	TC62	1.2 - 3.5mm	51mm	5.5mm	62mm	5 / 6" AF HEX
921199	TC75	1.2 - 3.5mm	65mm	5.5mm	75mm	5 / 6" AF HEX
920125	TC100	1.2 - 3.5mm	90mm	5.5mm	100mm	5 / 6" AF HEX
921202	TL32	4.0 - 12.5mm	12mm	5.5mm	32mm	5 / 6" AF HEX
921203	TL38	4.0 - 12.5mm	18mm	5.5mm	38mm	5 / 6" AF HEX
920128	TL50	4.0 - 12.5mm	30mm	5.5mm	50mm	5 / 6" AF HEX
921205	TS20	0.5 - 1.2mm	5mm	4.8mm	20mm	5 / 6" AF HEX

Product Range - Teks Screws - Grade A2-304 Austenitic Stainless Steel Self Drilling Screws

Eurocode	Code	Steel Thickness	Effective Thread Length	Diameter	Length	Head Style
921289	SC28	1.5 - 3.0mm	9mm	5.5mm	28mm	5 / 6" AF HEX
921291	SL45	4.0 - 10.0mm	18mm	5.5mm	45mm	5 / 6" AF HEX